

WAVE XLR

MICROPHONE INTERFACE & DIGITAL MIXING SOLUTION



EMBARGO DATE

July 15th, 2021

PRODUCT NAME / LISTING TITLE

Elgato Wave XLR – Mic interface, XLR/USB-C, anti-clipping, 75 dB preamp, phantom power, direct monitor, touch mute, Wave Link digital mixing app

MSRP

USD \$159.99 | CAD \$209.99 | €169.99 | £159.99

MARKETING ASSETS

<https://corsair.sharefile.com/f/fo5b4e44-5f64-4a50-a2e7-ed11eadce952>

PRODUCT DESCRIPTION

LONG:

Wave XLR does the work of multiple devices and packs features you won't find in conventional audio interfaces. Like proprietary Clipguard anti-distortion technology, a capacitive mute button, and integration with custom Wave Link mixing software. With up to 75 dB of ultra-low-noise gain, even notoriously insensitive dynamic mics sound loud and clear. 48 volts of phantom power bring condenser mics to life, and two switchable low-cut filters let you remove low frequencies for close and distant mic positions. You can even swap out the faceplate and control dial. Wave XLR — a compact USB interface that gives your mic superpowers.

MEDIUM:

A compact USB interface that gives your mic superpowers, Wave XLR packs features you won't find in conventional audio interfaces. Like proprietary Clipguard anti-distortion technology, a capacitive mute button, and direct integration with custom Wave Link mixing software. You can even swap out the faceplate and control dial.

SHORT:

A compact USB interface that gives your mic superpowers, Wave XLR features proprietary anti-distortion technology, swappable design components, and integration with custom mixing software.



WAVE XLR

MICROPHONE INTERFACE & DIGITAL MIXING SOLUTION

FEATURES

- Premium XLR to USB-C connection
- Use the Wave Link app to mix Wave XLR with multiple audio sources, plus create two independent mixes
- Proprietary Clipguard technology prevents microphone distortion
- Up to 75 dB of ultra-low-noise gain amplifies insensitive mics
- 48 V phantom power drives condenser microphones
- Dual selectable filters remove low frequencies
- High-power 3.5 mm headphone jack for clear zero-latency monitoring
- Capacitive mute button silences your mic feed upon the lightest touch
- Multifunctional control dial for mic gain, headphone volume, and mic / PC mix
- Faceplate and control dial can be swapped for different designs

TECHNICAL SPECIFICATIONS

- Frequency Response: 20 Hz - 20 kHz
- Dynamic Range: 100 dB (120 dB Clipguard engaged)
- Equivalent Input Noise (EIN): -130 dBV @ 60 dB gain
- Gain Range: 0 - 75 dB
- Phantom Power: 48 VDC, 7mA
- Maximum Input Level: 10 V @ 0 dB gain (Clipguard engaged)
- Maximum Output Level: 77 mW
- Resolution: 24-bit
- Sample Rate: 48 / 96 kHz
- Interface: USB-C

SYSTEM REQUIREMENTS

- Windows 10 (64-bit)
- macOS 10.15 or newer
- USB 3.0 or higher

WAVE XLR

MICROPHONE INTERFACE & DIGITAL MIXING SOLUTION



BOX CONTENTS

Wave XLR, USB-C Cable, Quick Start Guide

PRODUCT DIMENSIONS

3.47 x 4.63 x 3.31 in / 88 x 118 x 84 mm (depth x width x height)

PRODUCT WEIGHT

0.66 lb / 300 g

PACKAGING DIMENSIONS

7.52 x 6.10 x 3.74 in / 191 x 155 x 95 mm (depth x width x height)

PACKAGING WEIGHT

1.61 lb / 730 g

MASTER PACK QUANTITY

16

MASTER PACK DIMENSIONS

16.10 x 13.23 x 16.93 in / 409 x 336 x 430 mm (depth x width x height)

MASTER PACK SHIPPING WEIGHT

NW: 25.79 lb / 11.70 kg | GW: 29.32 lb / 13.30 kg

PALLET QUANTITY

256

WARRANTY

2 years

HARMONIZED TARIFF CODE

8518.40.2000

COUNTRY OF ORIGIN

CHINA

PART NUMBER | UPC | EAN

Part number: 10MAG9901 | UPC: 840006642886 | EAN: 0840006642886